

*2U rack mount SBC server chassis
with 1 x 5.25" + 1 x 3.5" + 1 x 3.5" (internal) drive bays*



Features

- Meets EIA RS-310C standard
- Heavy duty steel with Ni plating
- Slide rail applicable
- 6-slot PICMG butterfly backplane
- Replaceable air filter
- 2 x 8 cm high-speed ball-bearing fans for better ventilation
- Lockable door
- Front accessible PS/2 keyboard connector
- Easy assembly and maintenance

Specification

Construction

Heavy duty steel with Ni plating

Drive bays

1 x 5.25" + 1 x 3.5" + 1 x 3.5" (internal) drive bays

Cooling Fan / Air Filter

2 x 8 cm high-speed ball-bearing fans (2 x 39 CFM)

Replaceable air filter

Power Supply

Fit PS/2 type PSU

Main Board

6-slot PICMG butterfly backplane

System Indicator

1 x power on LED

1 x HDD LED

Front Panel Controls

1 x power on/off switch

1 x touch-free reset switch

1 x PS/2 keyboard connector

Operation Temperature

0 to 55 °C (32 to 131 °F)

Gross Weight

12.5 Kg (27.5 lb)

Dimension

424 mm (W) x 450mm (D) x 88 mm (H)

16.7" (W) x 17.7" (D) x 3.5" (H)

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579