

*4U rack mount storage server chassis
with 8x 5.25" + 1x 3.5" drive bays*



Features

- Meets EIA RS-310C standard
- Rugged design
- Slide rail applicable
- Three 12 cm high-speed hot-swappable ball-bearing fans for better ventilation
- 8 x 5.25" + 1 x 3.5" (or 1x slim CD-ROM & 1x slim FDD) open drive bays
- Fit 14 slot backplane or server board
- Fit PS/2 redundant PSU
- Easy assembly and maintenance
- Nickel plating

Specification

Construction

Heavy-duty steel with Ni plating

Drive bays

8 x 5.25" + 1 x 3.5" shock-resistant drive bays

Cooling Fan / Air Filter

3 x 12 cm hot-swappable high-speed ball-bearing fans (3 x 98 CFM)

Power Supply

Fit standard PS/2 type or PS/2 redundant ATX PSU

Mother Board

Fit 14 slot backplane

Fit full size ATX, WATX (13.0" x 12.0") M/Bs or dual-CPU server board

System Indicators

3 x HDD LED

1 x power on LED

Front Panel Controls

1 x power on/off switch

1 x touch-free reset switch

Operation Temperature

0 to 55 ° C (32 to 131 ° F)

Gross Weight

28 Kg (62lb)

Dimension

427mm(W) x 700mm (D) x 177mm (H)

16.8" (W) x 27.6" (D) x 7.0" (H)

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780
Tel:(714)368-3676 Fax:(714)368-9292
email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,
Da -an District, Taipei City, 106, Taiwan
Tel: 886-2-2707-9990 Fax: 886-2-2707-7579