


19 Slots (4xPCI) PICMG Back-plane

Features

- Fit for 19 slots chassis
- Support ATX and AT type power connector
- 2 x slots PICMG for SBC board
- 13 x ISA slots for full-size ISA boards
- 4 x PCI slots for full-size boards
- Well designed sufficient power is delivered to every slot



Specification

Connector:

PICMG: 2 x PICMG slots for SBC board.

ISA: 13 x ISA slots for full-size ISA board.

PCI:

- 4 x 5V 32-bit PCI slots for full-size boards on the primary bus.
- Those slots are Master/Slave configurable by using Bus Mastering Scheme.

AT connector: 1 x AT standard 12 pin power connector.

ATX connector: 1 x ATX standard 20 pin power connector.

ATX control connector:

- 1 x ATX control connector to distribute signals coming from the CPU board onto connector for soft on/off an ATX power supply.
- Pairs of header for local connection of a keyboard, fan power, and power LED.

PCB:

- The Printed Circuit Board's (PCB) overall dimensions are 265mm x 417mm (10.43" x 16.41"), and total thickness is 1.6mm.
- Mounting holes are provided and are located to conform to the baby AT form factor. Mounting Holes are connected to signal ground internally.

Standard:

- PCI-conforms to PICMG rev. 2.1 specification
- ISA-conforms to IEEE P996 specification

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780
Tel:(714)368-3676 Fax:(714)368-9292
email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,
Da -an District, Taipei City, 106, Taiwan
Tel: 886-2-2707-9990 Fax: 886-2-2707-7579