

*2U rack mount ATX server chassis  
with 1 x 5.25" + 1 x 3.5" + 2 x 3.5" (internal) drive bays*



### Features

- Meets EIA RS-310C standard
- Heavy duty steel with Ni plating
- Slide rail applicable
- 3-slot 32-bit riser card included (64-bit riser card option)
- Replaceable air filter
- 2 x 8 cm high-speed ball-bearing fans for better ventilation
- Lockable door
- Front accessible PS/2 keyboard connector
- Easy assembly and maintenance

### Specification

#### Construction

Heavy duty steel with Ni plating

#### Drive bays

1 x 5.25" + 1 x 3.5" + 1 x 3.5" (internal) drive bays

#### Cooling Fan / Air Filter

2 x 8 cm high-speed ball-bearing fans (2 x 39 CFM)

Replaceable air filter

#### PCI Expansion Slot

3-slot 32 bits riser card included (64 bits riser card option)

#### Power Supply

300 W ATX PSU

#### Main Board

Fit standard ATX, Micro ATX, Flex ATX M/Bs

#### System Indicator

1 x power on LED

1 x HDD LED

#### Front Panel Controls

1 x power on/off switch

1 x touch-free reset switch

1 x PS/2 keyboard connector

#### Operation Temperature

0 to 55 ° C (32 to 131 ° F)

#### Gross Weight

12.5 Kg (27.5 lb)

#### Dimension

424 mm (W) x 450mm (D) x 88 mm (H)

16.7" (W) x 17.7" (D) x 3.5" (H)

#### USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

#### Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579