

*4U rack mount server chassis with
3x 5.25" + 1x 3.5" + 1x 3.5" (internal) drive bays*



Features

- Meets EIA RS-310C standard
- Rugged design
- Two positions for card retainer
- Slide rail applicable
- 1 x 12 cm + 1 x 8 cm fan
- 3 x 5.25" + 1 x 3.5" + 1 x 3.5" (internal) shock-resistant drive bays
- Fit ATX M/B or 14-slot backplane
- Lockable front door
- Changeable I/O shield

Specification

Construction

Heavy duty steel

Drive bays

3 x 5.25" + 1 x 3.5" + 1 x 3.5" (internal) shock-resistant drive space

Cooling Fan / Air Filter

Front: 1 x 12 cm + 1 x 8 cm fans

Replaceable air filter

Power Supply

Fit PS/2 ATX PSU or PS/2 ATX redundant PSU

BackPlane / Main board

Fit for 14-slot backplane or ATX/AT main board

Speaker

1 x 8 speaker inside

System Indicators

Single system: 1 x HDD LED + 1 x power on LED

Dual system: 2 x HDD LEDs + 2 x power on LEDs

Front Panel Controls

Single system (default): 1 x power on/off switch , 1 x

system reset switch, and 1x K/B lock switch

Dual system: 2 x power on/off switches, 2 x system reset switches, and 2 x K/B lock switches

1 x PS/2 keyboard connector

Operation Temperature

0 to 55 °C (32 to 131 °F)

Gross Weight

15Kg (33lb)

Dimension

441 mm (W) x 450 mm (D) x 177 mm (H)

17.4" (W) x 17.7" (D) x 7.0" (H)

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579