

Compact high-capacity drive housing kit



Features

Compact high-capacity drive housing kit can hold slim-type drive/3.5" HDD within the standard 5.25" drive space

More flexible in limited drive space

Rugged design for industrial application

Integrated with slim-type drive/3.5" HDD (optional)

Standard desktop IDE & FDD connector

Standard 5.25" drive mounting holes

Specification

Construction

Heavy duty steel for industrial application

Drive Bays

External: 1 x slim-type drive

Internal: 1 x 3.5" HDD (optional)

Mounting Holes

Standard 5.25" drive holes reserved

Temperature and Humidity

Operating: 5-55 °C, 20-80%RH

Storage: -30-70 °C, 5-90%RH

Available Slim Drive

CD-ROM Drive -- 24X CD-ROM reading

DVD-ROM Drive -- 24X CD-ROM reading
-- 8X DVD-ROM reading

Combo-Drive -- 24X CD-ROM reading

-- 24X CD-R writing

-- 10X CD-RW writing

-- 8X DVD-ROM reading

Power Consumption

DVD-ROM: +5V@ 1.5A(MAX)

CD-ROM: +5V@ 1.5A(MAX)

Combo-Drive: +5V @ 1.3A (max)

MTBF

DVD-ROM: 60,000 POH

CD-ROM: 60,000 POH

Combo-Drive: 60,000 POH

Dimension

148.4 (W) x 155 (D) x 42 (H) mm

Weight

Gross: 0.9Kg

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579