

Compact intelligent drive housing kit (Slim CD-ROM+ Slim FDD)**Features**

Compact intelligent drive housing kit can hold slim-type DVD-ROM (or CD-ROM/CD-RW) /FDD/HDD within the standard 5.25" drive space

More flexible in limited drive space

Rugged design for industrial application

Quality device for high reliability

Integrated with slim type 8X DVD-ROM (24X CD-ROM/CD-RW) and floppy

Standard desktop IDE & FDD connector

Standard 5.25" Drive mounting hole

Specification**Construction**

Heavy duty steel for industrial application

Drive Bays

External: 1 x slim DVD-ROM or CD-ROM or CD-RW +
1 x NB FDD

(CD-RW speed:CD-R w 8X,r 20X ; CD-RW w 4X,r 14X
; CD r 24X)

Internal: 1 x NB 2.5" HDD (optional)

Mounting Holes

Standard 5.25" drive holes reserved

Temperature and Humidity

Operating: 5-55 °C, 20-80%RH

Storage: -30-70 °C, 5-90%RH

Power Consumption

DVD-ROM: +5V@ 1.5A(MAX)

CD-ROM: +5V@ 1.5A(MAX)

CD-RW +5V@ 1.8A(MAX)

FDD: +5V @ 0.8A (max) / 0.26A (typ) / 0.002A (stb)

MTBF

DVD-ROM: 60,000 POH

CD-ROM: 60,000 POH

CD-RW:50,000 POH

FDD: 15,000 POH

Dimension

148.4 (W) x 185 (D) x 42 (H) mm

Weight

Gross: 1.20Kg

USA Head Quarter

2681 Dow Ave., Suite A Tustin, CA 92780

Tel:(714)368-3676 Fax:(714)368-9292

email: info@racksolution.com

Taiwan sales office

16F-2, No.84, Sec 2, Fusing S. Rd.,

Da -an District, Taipei City, 106, Taiwan

Tel: 886-2-2707-9990 Fax: 886-2-2707-7579